



Features That Make a Difference

- Up to 32 channel Video Inputs
- Up to 4 SATA interface
- 200MBPS Video/Audio Incoming Bandwidth
- 200MBPS Video/Audio Outgoing Bandwidth
- Recording at up to 8 MP resolution
- Supports live view, storage, and playback at up to 8 MP resolution
- HDMI Video output up to 4K (3840 ×2160) resolution
- H.264/MPEG4 video formats
- Synchronous Playback upto 16-Ch.
- Audio I/O
- Alarms I/O

The Holis 32 channel network video recorder, HOLNVR32-IN offers superior value as it comes with 4 SATA interfaces for 4 HDDs. The NVR supports live view, storage, and playback of the connected cameras at up to 8MP resolution with a maximum incoming bandwidth of up to 200Mbps. The HDMI Video output is up to 4K (3840 ×2160) resolution with a maximum outgoing bandwidth of up to 200Mbps.

The Holis 32 channel network video recorder is an ideal and affordable solution for any small or medium scale surveillance application.

SPECIFICATIONS

Video/Audio input	
IP video input	32-ch
Incoming bandwidth	200 Mbps
Outgoing bandwidth	200 Mbps
Video/Audio output	
HDMI output resolution	4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA output resolution	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio output	1-ch, RCA (Linear, 1 KΩ)
Decoding	
Decoding format	H.264/MPEG4
Recording resolution	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	16-ch
Capability	2-ch @ 4K, or 8-ch @ 1080p
Hard disk	
SATA	4 SATA interfaces for 4HDDs
Capacity	500GB/1TB/2TB/3TB/4TB/5TB/6TB
External interface	
Two-way audio	1-ch, RCA (2.0 Vp-p, 1kΩ)
Network interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
Serial interface	1 RS-485 (half-duplex), 1 RS-232, 1 keyboard (optional)
USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
Alarm in/out	16/4
General	
Power supply	100 to 240 VAC
Power Consumption	≤ 80 W (≤ 20 W without hard disk)
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions (W × D × H)	445 × 390 × 70 mm (17.5" × 15.3" × 2.8")
Working Temperature	-10 °C ~ +55 °C (+14 °F ~ + 131 °F)
Working Humidity	10 to 90 %

COMPATIBLE HDD FOR HOLIS STANDARD – NVRs	
Model	Description
HOLNVR32-IN	Holis Standard 32- Channel NVR

WD (WESTERN DIGITAL) HARD DRIVE MODELS	
Capacity	Model
1TB	WD10EURX-63C57Y0
2TB	WD20EURS-63S48Y0
1TB	WD10EURX-63FH1Y0
1.5TB	WD15EURS-63S48Y0
3TB	WD30PURX
2TB	WD20PURX
6TB	WD60PURX-78T0ZY1
6TB	WD60PURX-64T0ZY1

SEAGATE HARD DRIVE MODELS	
Capacity	Model
500GB	ST3500312CS
500GB	ST3500410SV
500GB	ST3500411SV
750GB	ST3750330SV
1TB	ST1000VX000-9YW162
1TB	ST1000VM002-1CT162
1TB	ST1000VX001
1TB	ST1000NM0055
2TB	ST2000NM0055
2TB	ST2000VX003
2TB	ST2000VX000-9YW164
2TB	ST2000VX002-1AH166
2TB	ST2000VM003-1CT164
3TB	ST3000VX006
3TB	ST3000NM0055
3TB	ST3000VX000-1CU166
3TB	ST3000VX000-1CU166
3TB	ST3000VX000-1CU166
4TB	ST4000VX007
4TB	ST4000VX000
6TB	ST6000VX0023
6TB	ST6000VX0003
6TB	ST6000VX0011
6TB	ST6000VX0001

Ordering Information

SKU No.	Description
HOLNVR32-IN	Holis Standard 32- Channel NVR