

I-HIB2PI-LP

2MP IP Fixed Bullet Camera



KEY FEATURES



- Polycarbonate housing
- Up to 2MP, 1920×1080@30fps
- IH+265 /H.265 H.264B/H.264 M/H.264H
- Color:0.02Lux@(F2.0,AGC ON),B/W:0Lux with IR
- IR range up to 30m
- Built-in Mic
- Operating conditions -30°C~60°C(-22°C~140°C), ≤95%RH
- PoE:IEEE 802.3af,Max. 6W
- IP67

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.9"CMOS
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	>37dB
Angle Adjustment	0~360°(P); 0~80°(T); 0~360°(R)
LENS	
Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F2.0
Aperture Type	Fixed
Field of View	78.6°(H); 43.2°(V); 92.1°(D)
DORI Distance	Detect: 55.57m Observe: 22.05m Recognize: 11.11m Identify: 5.56m

ILLUMINATOR	
IR LEDs	2
IR Distance	Up to 30m
Wavelength	850nm
COMPRESSION STANDARD	
Video Compression	IH+265 /H.265 H.264B/H.264 M/H.264H
Video Bit Rate	32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz
IMAGE	
Max. Resolution	2MP,1920×1080@30fps
Main Stream	PAL:25fps(1920×1080, 1280×720, 704×576, 640×480) NTSC:30fps(1920×1080, 1280×720, 704×480, 640×480)
Sub Stream	PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters
Privacy Mask	4 black static areas
Defog	Yes
FEATURE	
General Alarm	Motion Detection
Exceptions Alarm	IP Address Conflict
NETWORK	
Protocols	HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; TLS v1.2; IPv4; Telnet; Unicast
System Compatibility	ONVIF(Profile S/T) RTSP
Remote Connection	≤2
Client	IH-VIEW
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
INTERFACE	
Communication Interface	1×RJ-45 (10/100 Base-T)
Built-in Mic	Yes
GENERAL	
Web Client Language	English
Operating Temperature	-30°C~60°C(-22°C~140°C)
Operating Humidity	≤95%RH
Storage Temperature	-30°C~60°C(-22°C~140°C)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	PoE:IEEE 802.3af,Max. 6W
Protection	Surge4000V; ESD6000V; IP67
Boundary Dimensions	167.8(L)94(W)94(H)mm
Package Dimensions	188 x 175x 110 mm
GrossWeight	0.3kg
Accessories	Including Bracket

DIMENSIONS (Unit: mm)



** Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.*

For more information,

<https://honeywellbuildings.in>

Tel: +91 124 4975000

Email: BuildingAutomation.SecurityIndia@honeywell.com

Honeywell Building Automation

Unitech Trade Center, 5th Floor, Sector-43,
Block C. Sushant Lok Phase - I.

Gurgaon - 122 002. Haryana India

<https://www.honeywellbuildings.in/>

I-HIB2PI-LP | 01 | 02/25
© 2025 Honeywell International Inc.

IMPACT
by Honeywell