

I-HIB4PI-VUL

4MP IP Motorized IR Bullet Camera

The IMPACT by Honeywell Motorized IR Bullet Camera Series I-HIB4PI-VUL variant is a 4MP Camera with 2.8-12mm lens, in a Bullet form factor. This economically priced camera features a built-in mic, for enhanced surveillance with the addition of an onsite audio. A superior IR range of 80mts ensures effective surveillance even in low ambient lighting, while its IH+265 compression reduces the bit rate, enabling faster streaming and lower storage needs.



FEATURES AND BENEFITS

- Polycarbonate Housing
- Min. illumination Color: 0.02Lux@F1.6
- DC12V,POE(802.3af)
- Up to 2688x1520@25fps
- Operating Conditions -30°C~60°C, 0~95% RH
- Motorized Lens 2.8-12mm
- IH+265/H.265/H.264
- IP67
- Support Tripwire and perimeter
- Built-In Mic, SD Card Slot, Reset Button
- Smart IR, IR Range: 80m

SPECIFICATIONS

MATERIAL SPECIFICATIONS	
CAMERA	
Image Sensor	1/2.9" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color: 0.02Lux@ (F1.6, ACG ON), B/W: 0Lux with IR
Day & Night	Dual IR Cut Filter with Auto Switch
Wide Dynamic Range	120 dB
Angle Adjustment	Pan 0°~360°,Tilt 0°~80°,Rotation 0°~360°
LENS	
Lens Type	Motorized
Focal Length	2.8-12mm
Lens Mount	Φ 14
Aperture Range	F1.6
ILLUMINATOR	
IR LEDs	4
IR Range	Up to 80m
Wavelength	850nm

INTERFACE	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Built-In Mic	Yes
Reset Button	Yes
On-board storage	Built-in MicroSD card slot, up to 512 GB
COMPRESSION STANDARD	
Video Compression	IH+265/H.264B/H.264M/H.264H
Video Bit Rate	32 Kbps~6Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz
IMAGE	
Max. Resolution	2688x1520
Main Stream	PAL:25fps(2688x1520,2560x1440,2304x1296,1920x1080,1280x720) NTSC:24fps(2688x1520,2560x1440)30fps(2304x1296,1920x1080,1280x720)
Sub Stream	PAL:25fps(704x576,704x288,352x288,640x360) NTSC:30fps(704x480,704x240,352x240,640x360)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/Incandescent lamp/Locked white balance
ROI	8 Region
OSD	16*16/32*32/48*48/64*64,adaptable size,Letters Such as Week,Date,Time,Total 1 Regions
Privacy Mask	Yes,4 Regions
Defog	Yes
NETWORK	
ANR	Yes
Protocols	HTTP,HTTPS,TCP/IP,UDP,UPnP,ICMP,DHCP,DNS,DDNS,Easy DDNS,NTP,QoS,IPv4,SSH,RTCP,ARP,RTSP
System Compatibility	Onvif Profile S/T/G
Remote Connection	2
Client	IH-View
Moblie Client	IH-View
Web	IE, Firefox, Edge, Safari, Chrome
FEATURE	
Alarm Trigger	Disk Full/Disk R/W Error/IP Address Conflict/Mask Alarm
Video Analytics	Support Tripwire and perimeter

GENERAL	
Web Client Language	English
Operating Conditions	-30°C~60°C, 0~95% RH
Storage Conditions	-30°C~60°C, 0~95% RH
Power Supply	DC12V±25%,POE(802.3af)
Power Consumption	≤ 7W
Protection	IP67
Boundary Dimensions	204(L)450(W)260(H)mm
Package Dimensions	215(L)95(W)120(H)mm
Gross Weight	0.57kg
Net Weight	0.42kg

* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.

For more information,

www.honeywellbuildings.in

Call: 000-8000-502167

Email: enquiry.mms@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002.

I-HIB4PI-VUL | 01 | 09/23
© 2023 Honeywell International Inc.

IMPACT
by Honeywell