

I-HNVR-1440

H.265 4HDD 40 Channel NVR

The new Impact series of Network Video Recorders (NVRs) is beneficial to customers who want a higher quality of video surveillance enhanced by HD and an advanced setup. This product can be used for video surveillance in banks, offices, manufacturing industries, warehouses, and parking lots – where image quality and clarity is a key priority. The smart features offered by the new Impact series of NVRs greatly help in the effective analysis of the video feed, while optimizing storage.



FEATURES AND BENEFITS

HD INPUT

- IH+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 40 channel input
- Supports live view, storage, and playback of the connected camera at up to 12MP resolution

HD TRANSMISSION

- 2×RJ45 self-adaptive 10/100/1000 Mbps network interfaces

HD OUTPUT

- HDMI and VGA simultaneous output
- HDMI Video output at up to 4K (3840 × 2160) resolution

HD STORAGE

- 4 SATA interfaces, up to 10TB for each HDD
- IH+265 compression effectively reduces the storage space and costs by up to 75%

VARIOUS APPLICATIONS

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc.
- VCA detection alarm is supported
- Smart search for the selected area in the video and smart playback to improve the playback efficiency
- Web6 supports plug-in free browsing and can preview videos on all browsers

SPECIFICATIONS

MATERIAL SPECIFICATIONS

INPUT

Video Input	40-ch
Max Resolution	12MP
Two-way Audio Input	1-ch, 3.5mm
Bandwidth	Income 200Mbps; Outgoing 200Mbps

OUTPUT


HDMI/VGA Output	HDMI 1-ch, 3840×2160, 2560×1600, 2560×1440, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800 VGA 1-ch, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800
Screen Split	1/3/4/6/8/9/10/13/16/20/25/36/40/64
Audio Output	1×RCA

DECODING


Decoding Format	IH+265/H.265/H.264
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Preview Capability	3x12MP, 4x8MP, 4x6MP, 5x5MP, 8x4MP, 9x3MP, 16x1080P, 32x720P, 40x4CIF
Synchronous Playback	3x12MP, 4x8MP, 4x6MP, 5x5MP, 8x4MP, 9x3MP, 16x1080P, 16x720P
Records Encryption	Yes
HARD DISK	
SATA	4 SATA interface for 2 HDDs
Capacity	Up to 10TB for each HDD
Array Type	JBOD, RAID0/1/5/6/10
EXTERNAL INTERFACE	
Network Interface	2xRJ45 self-adaptive 10/100/1000 Mbps network interface
USB Interface	1xUSB 2.0, 1xUSB 3.0
NETWORK	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, QoS, IPV4, IPV6, Multicast, ARP, UDP, SNMP, SSL, Telnet, RTMP, NFS
GENERAL	
Web Version	Web6
Language	English
Operating Conditions	-10°C~55°C, 10%~90% RH
Power Supply	100~240V AC, 50~60 Hz
Consumption (without HDD)	≤25W (without HDD)
Chassis	1.5U
Dimensions	75×347×440mm, (2.95×13.66×17.32 inch)
Weight (without HDD)	3.35Kg (7.38lb)

DIMENSIONS



PHYSICAL INTERFACES



For more information,

www.honeywellbuildings.in

Call: 000-8000-502167

Email: enquiry.mms@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002.

I-HNVR-1440 | 01 | 05/21
© 2021 Honeywell International Inc.

IMPACT
by Honeywell