

I-HPNVR-464

| 64CH 4 SATA NVR

The I-HPNVR-464 is a high-capacity NVR designed for extensive surveillance applications. Additionally, it includes multiple network interfaces, audio and alarm management capabilities, and supports various protocols for seamless integration. The device also supports advanced AI features such as face detection, pedestrian detection, and heat map analysis.



FEATURES AND BENEFITS



Up to 64 Channel Input



**4 Sata Interfaces,
Up To 18TB
(Enterprise Class Only)**



**H.265+/H.265/H.264
Video Formats**



**4 HDMI Port,1 VGA,
USB3.0*2, USB2.0*1
Support**



**2×RJ45 Self-adaptive
10/100/1000 Mbps
Network Interfaces**



**Supports live view,
storage and playback of the connected
camera at up to 12MP resolution**



**Connectable
to the Third Party
Network Cameras**

SPECIFICATIONS

VIDEO		
Resolution		12MP, 8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Incoming Bandwidth		640M
Outgoing Bandwidth		640M
PERFORMANCE		
Live Playback	Compression	Audio: G.711A/G.711U Video : H.264/H.265/H.264+/H.265+
	Frame rate	4K:240fps 4MP:480fps 2MP:960fps
	Event	MD(Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 16CH playback
	Fisheye	Support
UI/Monitoring	WEB	IE10/11, Safari V12.1 above, Firefox V52 above, Google chrome V57 above, Edge V.79 above

Support AI		Face Detection Pedestrian Detection Vehicle Detection Cross Counting Heat Map Crowd Density Detection Perimeter Intrusion Detection Line Crossing Detection Queue Legth Detection License Plate Detection Rare Sound Detection
------------	--	--

INTERFACE		
P/W Reset		Yes
Monitors	HDMI	3(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1920*1080, 1600*1200, 1920*1200, 840*2160/7680*4320/EDID) Async out *If the output resolution of HDMI 1 is set to 8K, the maximum output resolution of HDMI 3 and 4 will be limited to 1080P, and HDMI 2 will be disabled. 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 /EDID) Async out
	Ethernet	2 RJ45 100/1000 Base-T
	USB	USB2.0*1(front) , USB3.0*2(rear)
	Audio Out	1
	E-sata	1
	HDD	4 SATA HDD, up to 18TB (Enterprise-Class)
	Line in	1
	RS232	1*RJ45
	Rs485	1
	Alarm Input/out	16 in /1 out

GENERAL		
OSD Language		English
Mechanical Design	Dimension (WxDxH)	378*325.8*66mm
Electrical	Input Voltage/Current	12V/5A
	Power consumption (excluding hard disk)	8W
Environmental	Operating Temperature/ Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH

For more information,

www.honeywellbuildings.in

Call: 000-8000-502167

Email: enquiry.mms@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
 Block C, Sushant Lok Phase - I,
 Gurgaon - 122 002.

I-HPNVR-464 | 01 | 02/24
 © 2023 Honeywell International Inc.

IMPACT
 by Honeywell