





VL-SA74SX IP Video Door Phone Kit

Key Features:

- Handsfree Video Intercom
- 7-inch Wide Color Screen
- High-Definition Door Camera with 2MP Resolution
- Room to room intercom & Call Transfer Function Support.
- Multi Indoor (4) & Outdoor (2) Units Supported
- Weatherproof with IP65 Rating
- Vandal proof with IK08 Rating
- Color Night Vision with White LED
- 100 Image storage with built-in memory
- SD Card Support up 256 GB enables video recording function.
- RFID Card Unlock Support
- Electric Lock Integration
- Wi-Fi support* (2.4 GHz Only)
- IP CCTV Camera Integration through Wi-Fi.
- Alarm Sensor Integration* (up to 8 sensors)
- Motion Detection/Tamper Alerts from door station (outdoor unit).
- Home/Away/Sleep Modes
- Mobile App Access for iOS & Android (Panasonic SmartWiFi)
- Adjustable Camera Angle through Joystick.
- Exit Button & Door Status supported.

VL-SA74	VL-MA74 x 1, VL-VA504 x 1	
Model number and name	VL-MA74 Main Monitor Station (Main monitor) Extension Monitor	VL-VA504 Door Station (Doorphone)
Dimension (mm)	<div>Up to 4</div> <div>(including the main monitor)</div> 	<div>Up to 2</div> 
Power source	DC 14.5V 1A, 50/60 Hz / IEEE 802.3af Standard PoE	Power supplied by the main monitor over Cat6 / IEEE 802.3af Standard PoE
Power consumption	Standby: <3.0 W, Operating: <10.0 W	-
Power consumption	Standby: <3.0 W, Operating: <10.0 W	-
Dimensions (H x W x D) (Excluding protruding sections)	143 x 200 x 22 mm	150 x 95 x 41 mm
Weight	424 g	234 g
Operating environment	Ambient temperature: Approx. -20 °C to +40 °C Relative humidity (non-condensing): 10 % to 90 %	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %
Display	7-inch wide colour capacitive touchscreen (Approx. 17.8cm)	-
Monitor Resolution	1024 x 600	-
Operating System	Linux	-
Wi-Fi Connectivity	2.4 G Hz Only	-
Mobile App Supported	Panasonic SmartWiFi	-
Display language	English, Arabic	-
Talking method	Hands-free	-
Audio Quality	-	Noise Suppression, Echo Cancellation
Audio Input	-	Built-in Omnidirectional Microphone
Viewing angle	-	Diagonally: Approx. 155° Horizontally: Approx. 120° Vertically: Approx. 60°
Internal Memory	100 Images	-
External Memory	Max 256 GB SD Card Supported (Class 10 & Above)	-
Camera Resolution	-	1/2.9" CMOS with 2MP Lens
Stream Resolution (video)	1280 x 720 pixels	-
Stream Resolution (image)	1024 x 600 pixels	-
Installation method	Wall mount (mounting bracket supplied)	Surface mount (mounting base supplied)
Lock Connection Relay	1 Relay (No Com NC)	1 Relay (No Com NC)
Door Status Connection	-	1 NC Relay
Alarm Sensor	8	-
RFID Support	-	125 KHz RFID Support
Minimum illuminance required	-	1 lx (within approx. 50 cm from the camera lens)
Lighting method	-	White LED
IP rating / IK rating	-	IP65 / IK08

*Term and conditions apply.

Note: Product design specifications and colors are subject to change without notice to improve Reliability, Function or Design or otherwise. Errors and omissions excepted. Images displayed here are for illustration purposes only, actual product may vary.