


I-HPNVR-432

| 32CH 4 SATA NVR

The I-HPNVR-432 is designed for comprehensive surveillance applications. The NVR supports various video formats and resolutions, including up to 12MP, and is compatible with third-party network cameras. It offers intelligent analytics such as facial recognition, human detection, and license plate recognition. Additionally, it includes multiple network interfaces, audio and alarm management capabilities, and supports various protocols for seamless integration. The compact design, versatile connectivity options.



FEATURES AND BENEFITS



Up to 32 Channel Input



**4 Sata Interfaces,
Up To 12TB
(Enterprise Class Only)**



**H.265+/H.265/H.264
Video Formats**



**2 HDMI Port,1 VGA,
USB3.0*2, USB2.0*1
Support**



**2×RJ45 Self-adaptive
10/100/1000 Mbps
Network Interfaces**



**Supports live view,
storage and playback of the connected
camera at up to 12MP resolution**



**Connectable
to the Third Party
Network Cameras**

SPECIFICATIONS

VIDEO	
Incoming Bandwidth	320M
Outgoing Bandwidth	320M
PERFORMANCE	
Recording Resolution	12 MP/8 MP/5 MP/4 MP/3 MP/1080p/720p
Recording Compression	Audio: G.711a,G.711u Video : H.264/H.265, H.264+/H.265+
Speed	12MP:30fps 8MP:120fps 4MP:240fps 2MP:480fps
Playback	1080P:480fps Max 16CH
NETWORK	
WEB	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Protocols	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, UPnP, HTTP, HTTPS
API	Onvif (profile S/G/T)

INTERFACE	
VGA	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440(2K), 3840*2160(4K)) 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 / EDID) Async out
Ethernet	2 RJ45 100/1000 Base-T
USB	USB2.0*1(front), USB3.0*1+USB2.0*1(rear)
Audio	1 in / 1 out
E-sata	1
HDD	4, each up to 12TB
Rs485	1
Alarm Input/out	16 in / 1 out
GENERAL	
OSD Language	English
Dimension (WxDxH)	378*326*66mm
Weight	2300g
Input Voltage/Current	12V/5A
Power consumption (excluding hard disk)	8W
Operating Temperature/Humidity	Temperature :-10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH

For more information,

www.honeywellbuildings.in

Call: 000-8000-502167

Email: enquiry.mms@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002.

I-HPNVR-432 | 01 | 02/24
© 2023 Honeywell International Inc.

IMPACT
by Honeywell