





VL-SA611SX

Hybrid Video Door Phone Kit with Mobile App Access

Key Features:

- Handsfree Video Intercom
- 7-inch Wide Color Screen
- High-Definition Door Camera with 2MP Resolution
- Room to room intercom & Call Transfer Function Support.
- Multi Indoor (4) & Outdoor (2) Units Supported
- Weatherproof with IP65 Rating
- Vandal proof with IK08 Rating
- Color Night Vision with White LED
- 100 Image storage with built-in memory
SD Card Support up 256 GB enables video recording function
- Electric Lock Integration
- Wi-Fi support* (2.4 GHz Only)
- IP CCTV Camera Integration through Wi-Fi.
- Motion Detection/Tamper Alerts from door station (outdoor unit).
- Home/Away/Sleep Modes
- Mobile App Access for iOS & Android (Panasonic SmartWiFi)
- Adjustable Camera Angle through Joystick.

VL-SA611	VL-MA611 x 1, VL-VA511 x 1	
Model number and name	VL-MA611	VL-VA511
	Main Monitor Station (Main monitor) Extension Monitor	Door Station (Doorphone)
Dimension (mm)	<div>Up to 4</div> <div>(including the main monitor)</div> 	<div>Up to 2</div> 
Power source	DC 14.5V 1A, 50/60 Hz	Power supplied by the main monitor
Power consumption	Standby: <3.0 W, Operating: <10.0 W	-
Dimensions (H x W x D) (Excluding protruding sections)	143 x 200 x 22 mm	150 x 95 x 41 mm
Weight	408 g	226 g
Operating environment	Ambient temperature: Approx. -20 °C to +40 °C Relative humidity (non-condensing): 10 % to 90 %	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %
Display	7-inch wide colour capacitive touchscreen (Approx. 17.8cm)	-
Monitor Resolution	1024 x 600	-
Operating System	Linux	-
Wi-Fi Connectivity	2.4 G Hz Only	-
Mobile App Supported	Panasonic SmartWiFi	-
Display language	English, Arabic	-
Talking method	Hands-free	-
Viewing angle	-	Diagonally: Approx. 155° Horizontally: Approx. 120° Vertically: Approx. 60°
Internal Memory	100 Images	-
External Memory	Max 256 GB SD Card Supported (Class 10 & Above)	-
Camera Resolution	-	1/2.9" CMOS with 2MP Lens
Stream Resolution (video)	1024 x 600 pixels	-
Stream Resolution (image)	1024 x 600 pixels	-
Installation method	Wall mount (mounting bracket supplied)	Surface mount (mounting base supplied)
Lock Connection Relay	1 Relay (No Com NC)	1 Relay (No Com NC)
Minimum illuminance required	-	1 lx (within approx. 50 cm from the camera lens)
Lighting method	-	White LED
IP rating / IK rating	-	IP65 / IK08

*Term and conditions apply.

Note: Product design specifications and colors are subject to change without notice to improve Reliability, Function or Design or otherwise. Errors and omissions excepted. Images displayed here are for illustration purposes only, actual product may vary.